

5215-SPB EXIT RELEASE PUSH BUTTONS


Positive Release

Highly Visible

Illuminated Button

SPDT Contacts

**Compliant with
NFPA & BOCA
Codes for
Access Controlled
Egress Doors**



High Visibility Push Button

The 5215-SPB series push button assemblies provide a clearly visible means of actuating electric locking release. These, easy to operate, request-to exit controls are ideal for use in any facility with access controlled entry/exit.

Standard Single Gang Mounting

These push button switches are supplied with a brushed stainless steel plate for mounting on a standard single gang 2" x 4" electrical box. The switch contact block requires only 2-1/4" depth within the mounting cavity.

Illuminated Square Actuator Button

The 1-1/2" x 1-1/2" illuminated button can be easily recognized when powered. The lamp is rated at 28 VDC for long life.

LED Status Indicator

A red LED is available, as an option, to be mounted above the square actuator button. This can be utilized to provide indication of door lock status.

Heavy Duty Contacts

The SPDT contacts on the momentary action switch are rated for 10 amps at 125/250 VAC. Color coded, 7" leads are easily connected to field wiring.

Optional Text Graphic



The illuminated actuator button is also available with "EXIT" text. The block lettering in black is clearly visible against the green background when the back-light is on or off.

NFPA / BOCA Code Compliance

An optional FT-Timer is available for use with R-E-X motion detector applications requiring compliance with NFPA and BOCA codes. These units provide a fixed 30 second unlock time whenever the push button actuator is depressed and then released.

5215-SPB SERIES ILLUMINATED PUSH BUTTONS

SQUARE ILLUMINATED BUTTON ON STAINLESS STEEL SINGLE GANG PLATE




AVAILABLE ONLY WITH SPDT MOMENTARY ACTION SWITCH RATINGS - 10 AMPS @ 125/250 VAC

LAMP RATING
28VDC MAX

BLUE
BLUE

LED RATING
28VDC MAX

RED +
BLACK -



Model Descriptions

5215-SPB = Square Illuminated Push Button Momentary SPDT Switch mounted on Single Gang Plate.

Options

- xL = Optional Red LED mounted above Square Push Button.
- xE1 = Optional Text "PUSH TO EXIT" Standard Black Letters on Green.
- xE3 = Optional Text "EXIT" Standard Black Letters on Green.
- xAT = DPDT-Electronic Timer Module 2 - 60 Second Adjustable
- xFT = DPDT-Electronic Timer Module 30 Second Fixed Delay

Specifications

- Physical Size
Switch Plate - Single Gang 2-3/4" wide x 4-1/2" high x 2-1/4" deep (including contact block)
- Push Button - Illuminated 1-1/2" x 1-1/2" Square Momentary Action
- Optional LED - Standard Red Diffused T-1-3/4 LED with Twin Leads.

Electrical

- Contacts - Momentary SPDT action (P15) rated 10 amps @ 125/250 VAC.
- Lamp - Incandescent 28 VDC maximum.
- LED - Red LED - 28 VDC maximum.

Economical Switch Control

This low-cost push button control will meet the requirements of most access control systems for request-to-exit devices. The illuminated square button is highly visible recognized exit device.

Quick Installation

Installation is fast, mounting the switch plate to a standard single gang electrical box. Long 7" color coded leads ease wiring hook-up.

Distributed by:



**DORTRONICS
SYSTEMS, INC.**

1668 SAG HARBOR TURNPIKE, SAG HARBOR, NY 11963
www.dortronics.com - (800) 906-0137 - (631) 725-8148 FAX